ET 4201976648US

# TRANSFERRING A CALL TO A BACKUP ACCORDING TO CALL CONTEXT

## CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following co-pending applications:

(1) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010818US1);

(2) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010819US1);

(3) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010820US1);

(4) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010821US1);

(5) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010822US1);

(6) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010823US1);

(7) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010824US1);

(8) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010825US1);

(9) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010826US1);

(10) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010827US1);

(11) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010830US1);

(12) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010832US1);

(13) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010833US1);

(14) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010834US1);

(15) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010835US1); and

(16) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010837US1).

# BACKGROUND OF THE INVENTION

## 1. Technical Field:

The present invention relates in general to
telecommunications and, in particular, to voice identification.
Still more particularly, the present invention relates to
identifying a backup for a call according to the call context.

## 2. Description of the Related Art:

Telephone service has created communication channels
worldwide, and those channels continue to expand with the advent
of cellular and other wireless services.  A person can simply
take a telephone off-hook and dial a destination number or press
a send button and be connected to a telephone line around the
world.

Messaging systems have developed that answer a line after a
set number of rings or a  designated period of time.  An
answering machine device may connect to a telephone device to
answer incoming calls.  Alternatively, an answering machine
service, provided by a telephone service provider, answers the
call and provides options for a caller to leave a message in a
voice mail box or through text messaging, for example.

Within private telephone switching systems, each telephony
device may be provided with buttons or other selection options
that an individual may utilize to select a reason the caller is
unavailable.  An operator attempting to connect a caller to that
individual will receive the unavailable signal and reason for

unavailability, such that the operator may then switch the caller to a voice mail box or to another available employee.

An advantage of messaging systems within a private telephone switching system is that an individual may provide a message to callers that indicates a backup in the case that the caller needs to talk with an someone rather than leaving a message. Additionally, within a private telephone switching system, callers are typically provided with the option of pressing A0" during the message to have the call transferred to the operator or an assistant.

However, a limitation of messaging systems within a private telephone switching system is that a backup accessible according by pressing A0" or another entry is limited to a line number accessible within the private telephone switching system.  A single backup within a private telephone switching system is limited because callers may try to reach an individual at a business line within a private switching system concerning non-business matters, where the individual's backup within the company is not helpful.  While the individual may provide a message to callers that details a backup and telephone number of that backup for non-business matters, the caller is then required to end the call and dial the number of that backup.

A limitation of messaging systems in general is that an individual typically cannot designate a backup unless the line number is connected to a private telephone switching system.  An individual may indicate in an entry message that names and phone numbers of backups for the caller. However, an individual typically records one message that is played for all incoming calls, where that message will then reveal those names and

numbers to any caller reaching the messaging system.

Forwarding services allow an individual to select a line number to which incoming calls are automatically forwarded. Forwarding systems allow an individual to have calls follow them to the line number most accessible to the caller. Alternatively, an individual may forward calls to a line number accessible to a backup for the individual. However, forwarding systems are limited in that only a single line may be selected for forwarding calls to, regardless of the context of the call. This limitation is apparent where an individual selects to forward calls from a business line to a colleague's business line. A personal call made to the individual's business line will be forwarded to the colleague, rather than transferred to a messaging system.

Therefore, in view of the foregoing, it would be advantageous to provide a method, system, and program for providing a backup for calls, whether or not the line number is managed by a private telephone switching system. In addition, it would be advantageous to provide a method, system, and program for providing multiple single entry backup selections for a call. Morever, it would be advantageous to provide a method, system, and program for automatically forwarding a call to a backup or automatically transferring the call when the individual is unavailable, where that backup is automatically selected based on the context of a call.

## SUMMARY OF THE INVENTION

In view of the foregoing, it is therefore an object of the present invention to provide an improved telecommunications system.

It is another object of the present invention to provide a method, system and program for improved voice identification.

It is yet another object of the present invention to provide a method, system and program for identifying a backup for a call according to the call context.

According to one aspect of the present invention, a context for a call from a caller to an intended callee is detected. An intended party backup profile is accessed that indicates multiple backup parties designated by the intended callee. At least one backup party is automatically selected from among the multiple backup parties according to the context for the call. The call may be automatically forwarded to at least one backup party if the intended callee has currently elected to forward calls. Alternatively, after detecting that the intended callee is unavailable, the call may be automatically transferred to at least one backup party.

In particular, a trusted telephone network preferably processes the call and initiates a context inference service to identify the context of a call. The context inference service may be initiated locally within the trusted telephone network or at a server located outside the trusted telephone network, with additional security applied for the communication channel.

All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

## BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims.  The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

**Figure 1** depicts a block diagram of a network environment in which the present invention may be implemented;

**Figure 2** illustrates a block diagram of an identity authentication and context inference system in accordance with the method, system, and program of the present invention;

**Figure 3** depicts a block diagram of the flow of a call through a context inference system in accordance with the method, system, and program of the present invention;

**Figure 4** illustrates an illustrative example of a context based caller backup selection in accordance with the method, system, and program of the present invention;

**Figure 5** depicts a block diagram of a context inference service in accordance with the method, system, and program of the present invention;

**Figure 6** illustrates a flow diagram of a signal flow and processing of a call in accordance with the method, system, and program of the present invention; and

Figure 7 depicts a high level logic flowchart of a process and program for controlling a context inference service in accordance with the method, system, and program of the present invention.

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A method, system, and program for identifying a backup for a call according to the call context are provided. For purposes of the present invention, context may include, but is not limited to, the identity of the caller or callee, the device identity and owner, the location of the caller and callee, the path of a call, and billing information for the caller and callee. Location of the caller and callee may include, but is not limited to, the time zone, country, state, city, building location, or GPS location of a caller or callee.

For purposes of the present invention, a backup may include, but is not limited to, a line number, a backup identity, a messaging service, a forwarding service, a private switching system operator, an instant messaging system, a text messaging system, and a web page address. In addition, other types of backups may be selected by an individual.

The present invention is preferably performed by a context inference service located within an Intelligent Peripheral of the trusted telephone network and/or located within a Telco Application service outside the trusted telephone network. As will be further described, the Telco application service located outside the trusted telephone network is enabled to provide services to callers and callees via enhanced security channels.

The identity of the caller is preferably authenticated and utilized by the context inference service to determine a backup when the intended callee is unavailable. In particular, a callee may be associated with a dialed line number. Alternatively, the caller may enter the intended callee identity. Further, an

messaging service that answers the call may provide the caller
with the option to select from at least one callee, where the
messaging service then switches the call to a context based
backup for the intended callee.  Preferably, whatever the case, a
backup profile for the intended callee is accessed, where the
backup profile includes backup preferences according to the
context of the call.

In particular, the context inference service may
automatically determine a context backup for the call and forward
the call to the context backup if the intended callee has
requesting that calls be forwarded.  In addition, the context
inference service may automatically determine the context backup
for the call and transfer the call to that backup if the intended
call is determined to be unavailable.  Alternatively, a caller
may be prompted to select a context backup, where each context
backup is selectable by the caller by a single keypad or voice
entry, such as A1@.  The context inference service then forwards
or transfers the call to the line number associated with the
selected backup.

The identity of the callee answering the call is also
preferably authenticated.  In particular, since the call is being
transferred from the intended callee, it is particularly
advantageous to identity the party answering the call for the
caller.

Identity authentication is preferably performed by
authenticating the voices of the caller and callee, however other
biometric input may also be utilized for identification.
Identity authentication may be initiated by the origin device
originating the call, the intermediary device processing the

call, or the destination device receiving the call.  Each of the
devices may access a third party or external server to perform
the identity authentication.  Performance of identity
authentication has different advantages depending on the device
initiating the identity authentication.

While in the present invention, authentication of a caller
or callee identity is described with emphasis placed on voice
authentication, other methods of caller and callee identity
authentication may also be performed.  Voice samples utilized for
voice authentication are just one of multiple types of biometric
sampling.  For example, a caller or callee may locally provide an
eye scan, a fingerprint, and other biophysical identifiers that
are transmitted within or outside the trusted network to
authenticate the identity of the caller or callee.

Other context information is received, determined and
inferred from context clues.  Context clues may include the
identities of the caller and callee, the line numbers, the line
subscriber profiles, caller/callee profiles, and other parameters
associated with the call.  As a call is transferred and
forwarded, context clues for each portion of a call path are
gathered and utilized to update the context of the call.

For purposes of the present invention, telephony devices are
termed origin devices when utilized for origination of a call to
an intermediary device and are termed destination devices when
utilized for receipt of a call from an intermediary device.
Subscribers to a call are termed callers when originating a call
and are termed callees when receiving a call.  Callers and
callees may or may not be line subscribers to the particular
telephony device utilized.

In the following description, for the purposes of explanation, numerous specific details are set forth to provide a thorough understanding of the present invention.  It will be apparent, however, to one skilled in the art that the present invention may be practiced without these specific details.  In other instances, well-known structures and devices are shown in block diagram form to avoid unnecessarily obscuring the present invention.

With reference now to the figures, and, in particular, with reference now to **Figure 1**, there is depicted a block diagram of a network environment in which the present invention may be implemented.  While the present invention is described with reference to one type of network environment, it will be understood by one with skill in the art that the present invention may be implemented in alternate types of network environments.

First, the network environment incorporates a Public Switching Telephone Network (PSTN) **10**.  As is known in the art the core of PSTN **10** may include multiple telephone networks, each owned by one of multiple independent service providers.  Each telephone line is carried by an independent service provider within PSTN **10** and is typically assigned to at least one subscriber.

Switching of a call within an independent service provider's telephone network is considered trusted movement within a trusted network because the call remains within the company's telephone network infrastructure.  However, calls may be transferred from one service provider's telephone network to another service

provider's telephone network in generally trusted movement.
Generally, service providers are in competition with one another
and therefore there is general trust in transferring a call, but
not trust in sharing of subscriber information beyond a
subscriber number and name from one service provider to the next
without security features or other arrangements.

Advantageously, each telephone network within PSTN **10** may
access a data network functioning as an extension to PSTN **10** via
an Intranet.  Data networks may include, for example, subscriber
profiles, billing information, and preferences that are utilized
by a service provider to specialize services. Transfer of
information between a service provider's data network and
telephone network is trusted movement in sharing of information.

Further, each telephone network within PSTN **10** may access
server systems external to PSTN **10** in the Internet Protocol over
the Internet or an Intranet.  Such external server systems may
include an enterprise server, an Internet service provider (ISP),
an access service provider (ASP), a personal computer, and other
computing systems that are accessible via a network.  In the
present embodiment, transfer of information between PSTN **10** and
server systems accessible via a network **20** is untrusted and
therefore may require verification and additional security.
Network **20** may be preferably considered an external network.

In the present invention, network **20** may comprise a private
network, an Intranet, or a public Internet Protocol network.
Specifically, telco application server **22**, generic application
server **24**, pervasive application server **26**, and systems
management server **28** represent server systems external to PSTN **10**

that may be accessed by PSTN **10** over network **20**.

In particular, telco application server **22** preferably includes multiple telco specific service applications for providing services to calls transferred to a server external to PSTN **10**.  In particular, a call may be transferred from PSTN **10** to telco application server **22** to receive at least one service and then the call is transferred back to PSTN **10**.  PSTN 10 preferably brokers the connection between the telephony device and telco application server **22**.  Such services may also be provided to calls within PSTN **10**, however placing such services at a third party such as telco application server **22,** is advantageous because adding services and information to PSTN **10** is time consuming and costly when compared with the time and cost of adding the services through telco application server **22**.

In accord with an advantage of the present invention, as will be further described, the identity of both the caller and the callee may be authenticated by one of telephony devices **8a-8n**, PSTN **10,** or by telco application server **22**.  By authenticating the actual identity of the person making a phone call and the person receiving the phone call, rather than the identification of a device from which a call is made and received, an enhanced specialization of services to subscribers may be performed.

An authentication service within telco application server **22** may include identification and verification of the identity of a caller and/or callee of a particular call.  Such a service may require that subscribers provide voice samples when setting up a subscription.  The stored voice samples may then be compared

against voice samples received for a particular call in order to authenticate the identity of a current caller or callee of the particular call.

Generic application server **24** preferably accesses independent server systems that provide services.  For example, a messaging server, a financial server, an Internal Revenue Service (IRS) server, and database management system (DBMS) server may be accessed in HTTP via network **20**.  Each of these servers may include a telco service application that requires authentication of the subscriber before access is granted.  For example, a financial server may provide a telco service application that allows an authenticated subscriber to access current financial records and request stock quotes from the financial server.

Pervasive application server **26** manages services for wirelessly networked devices.  In particular, pervasive application server **26** preferably handles distribution of wireless packets of voice and data to wirelessly networked devices utilizing a standard such as short messaging service (SMS) messaging or other 3G standards.

Systems management server **28** manages subscriber personalization via the web.  In particular, systems management server **28** includes browser technology that includes a provisioning console **30** for establishing a subscriber profile and a management console **32** for managing and updating the subscriber profile.  A subscriber preferably accesses the consoles of systems management server **28** via the Internet utilizing a computing system, such as computing systems **34a-34n.**

The subscriber profile may be accessed at systems management server **28** by other external servers and PSTN **10** via network **20**. In addition, a local copy of a subscriber profile updated in systems management server **28** may be stored within a particular service provider's data network or telephone network.  Each service provider may specify the types of preferences and other information included within a subscriber profile.

In particular, a subscriber may provide a voice imprint when establishing a subscriber profile through provisioning console **30**.  Other types of authentication information may also be provided including, but not limited to, a password, an eye scan, a smart card ID, and other security devices.  In addition, a subscriber may designate billing preferences, shopping preferences, buddy list preferences, and other preferences that enable specialized service to the subscriber when the subscriber's identity is authenticated from the voice imprint or other identification.

Advantageously, a management agent is built into each external server to monitor the services provided by each server according to the authenticated subscriber receiving the services. By monitoring service output according to subscriber, the subscriber may then be billed according to each use of a service.

PSTN **10** preferably includes both voice and data signaling networks that interface with network **20** via gateways.  Each of the gateways acts as a switch between PSTN **10** and network **20** that may compress a signal, convert the signal into Internet Protocol (other protocol) packets, and route the packets through network **20** to the appropriate server.

In particular, the voice network interfaces with network **20** through media gateway **14** which supports multiple protocol gateways including, but not limited to, SIP.  SIP is a signaling protocol for Internet conferencing, telephony, presence, events notification and instant messaging.

In addition, in particular, the data signaling network interfaces with network **20** through signaling gateway **12** which supports multiple protocol gateways including, but not limited to, parlay protocol gateways and SS7 protocol gateways.  Internet servers, such as telco application server **22** may include protocol agents that are enabled to interact with multiple protocols encapsulated in Internet Protocol packets including, but not limited to, SS7 protocol, parlay protocol, and SIP.

Looking into PSTN **10**, a telephone network typically includes multiple switches, such as central office switches **11a-11n**, that originate, terminate, or tandem calls.  Central office switches **11a-11n** utilize voice trunks for transferring voice communications and signaling links for transferring signals between signaling points.

Between signaling points, one central office switch sends signaling messages to other central office switches via signaling links to setup, manage, and release voice circuits required to complete a call.  In addition, between signaling points, central office switches **11a-11n** query service control points (SCPs) **15** to determine how to route a call.  SCPs **15** send a response to the originating central office switch containing the routing number(s) associated with the dialed number.

SCPs **15** may be general purpose computers storing databases of call processing information.  While in the present embodiment SCPs **15** are depicted locally within PSTN **10**, in alternate embodiments SCPs **15** may be part of an extended network accessible to PSTN **10** via a network.

One of the functions performed by SCPs **15** is processing calls to and from various subscribers.  For example, an SCP may store a record of the services purchased by a subscriber, such as a privacy service.  When a call is made to the subscriber, the SCP provides record of the privacy service  to initiate an announcement to a caller to identify themself to the subscriber with the privacy service who is being called.  According to an advantage of the invention, authentication of the subscriber receiving the call may be required before the privacy service is initiated for that subscriber.

In particular, network traffic between signaling points may be routed via a packet switch called an service transfer point (STP) **13**.  STP **13** routes each incoming message to an outgoing signaling link based on routing information.  Further, in particular, the signaling network may utilize an SS7 network implementing SS7 protocol.

Central office switches **11a-11n** may also send voice and signaling messages to intelligent peripherals (IP) **17** via voice trunks and signaling channels.  IP **17** provides enhanced announcements, enhanced digit collection, and enhanced speech recognition capabilities.

According to an advantage of the present invention, the

identity of a caller is authenticated according to voice
authentication./ Voice authentication is preferably performed by
first identifying a subscriber by matching the name or other
identifier spoken with a subscriber name or identifier.  Next,
voice authentication requires verifying that the voice audio
signal matches that of the identified subscriber.  However, in
alternate embodiments, the identity of a caller may be
authenticated according to passwords, eye scans, encryption, and
other security devices./

     In particular, to perform subscriber authentication of audio
signals received from callers, IP **17** may include storage for
subscriber specific templates or voice feature information, for
use in authenticating subscribers based on speech.  If a
subscriber specific template is not stored on a local IP **17**, then
a remote IP containing the subscriber specific template may be
accessed via a network.  In addition, local IP **17** may access
systems management server **28** or another repository for voice
imprints to access the subscriber specific template.

     Where IP **17** authenticates the identity of a caller (e.g. the
subscriber placing a call), a voice identifier (VID) representing
the authenticated caller identity is transferred as a signal for
identifying the caller.  In addition, where IP **17** authenticates
the identity of a callee (e.g. the subscriber receiving a call),
a reverse VID (RVID) including the callee identity is transferred
as a signal for identifying the callee.

     Alternatively, to perform subscriber authentication of audio
signals received from callers, PSTN **10** may broker a caller
identity authentication service from telco application server **22**.

In particular, a signaling channel is opened between central
office switches **11a-11n** and telco application server **22** via
signaling gateway **12**.  In addition, a voice channel is opened
between central office switches **11a-11n** and telco application
server **22** via media gateway **14**.

Because telco application server **22** is located outside of
the trusted network, there may be a time delay associated with
establishing a connection to telco application server **22** and
authenticating the identity of a caller that is longer than a
time delay present where a caller identity is authenticated by IP
**17**.

In addition, because telco application server **22** is located
outside of the trusted network, it is advantageous to establish a
level of security for transactions between telco application
server **22** and central office switches **11a-11n**, wherein the level
of security is suitable for untrusted communications.  A level of
security may be implemented by utilizing security based
protocols, such as the secure socket layer, and by applying
ordinary encryption.  In particular, the level of security
preferably protects the communication channel between telco
application server and PSTN **10** and authenticates the identity of
the server from which a caller identity authentication service is
accessed.  Therefore an additional feature of signaling gateway
**12** and media gateway **14** is security verification.

Advantageously, VIDs indicate through text, voice, or video
the identity of a caller.  For example, a caller's name may be
transferred as the identity of a caller.  Alternatively, a video
clip stored with the subscriber template may be transferred as

the identity of a caller.  Additionally, VIDs may indicate the
identity of the device utilized by a caller to provide context
for a call.  Further, VIDs may indicate which system or systems
have authenticated the caller identity.

After a VID and/or RVID are determined by IP **17**, IP **17** and
SCP **15** may communicate to designate which services are available
according to VID and RVID.  Advantageously, by designating
services according to a VID and/or RVID, subscribers are provided
with services and billed for those services independent of the
devices utilized by subscribers.  In particular, a 1129 protocol
or other protocol may be utilized to enable signal communications
between IP **17** and SCPs **15**.

In addition, as previously described, caller authentication
to determine VIDs and RVIDs may be performed by an external
system, such as telco application server **22**.  The VID or RVID
returned from telco application server **22** may be transferred from
central office switches **11a-11n** to SCP **15** in order to access a
subscriber profile associated with the VID or RVID.
Alternatively, the VID or RVID may first transfer to IP **17**, where
additional verification of the caller identity is performed.  For
example, IP **17** may control distribution of the VID to the caller,
where the caller is prompted to enter a password or additional
information.  IP **17** may then initiate loading the caller profile
into central office switches **11a-11n** if the additional caller
input is verifiable for the VID.

An origin telephony device or destination telephony device
may also determine a VID and/or RVID for the caller and/or callee
of a call.  In particular, telephony devices **8a-8n** and call

centers **16a-16n** may function as origin and destination telephony devices. Each of the telephony devices may include a database of voice templates that may be matched to authenticate the identity of a caller or callee. In addition, each of the telephony devices may access a third party, such as telco application server **22**, to authenticate the identity of the caller or callee. In either case, the telephony device transmits a VID and/or RVID with a call to PSTN **10**.

Telephony devices **8a-8n** may include, but are not limited to wireline devices, wireless devices, pervasive device equipped with telephony features, a network computer, a facsimile, a modem, and other devices enabled for network communication. Advantageously, as previously described, a voice authentication functioning device may be included in each of telephony devices **8a-8n**.

In addition, telephony devices **8a-8n** may each incorporate a display that provides a visual output of a VID or RVID. Alternatively, such a display may be provided in a separate device connected to the line in parallel to telephones **8a-8n**. According to one advantage of the present invention, the identity of the actual caller or actual callee are output to a display in association with a call. In addition, other context information about the caller including, but not limited to, the device from which the call originates or is answered, ratings for a caller or callee, and other context information may be output to a display in association with a call.

Telephony devices **8a-8n** are communicatively connected to PSTN **10** via wireline, wireless, ISDN, and other communication

links.   Preferably, connections to telephony devices **8a-8n**
provide digital transport for two-way voice grade type telephone
communications and a channel transporting signaling data messages
in both directions between telephony devices **8a-8n** and PSTN **10**.

In addition to telephony devices **8a-8n**, advanced telephone
systems, such as call centers **16a-16n**, may be communicatively
connected to PSTN **10** via wireline, wireless, ISDN and other
communication links.   Call centers **16a-16n** may include PBX
systems, hold queue systems, private network systems, and other
systems that are implemented to handle distribution of calls to
multiple representatives or agents.

Returning to central office switches **11a-11n**, typically, one
central office switch exists for each exchange or area served by
the NXX digits of an NXX-XXXX (seven digit) telephone number or
the three digits following the area code digits (NPA) in a ten-
digit telephone number.   The service provider owning a central
office switch also assigns a telephone number to each line
connected to each of central office switches **11a-11n**.   The
assigned telephone number includes the area code (NPA) and
exchange code (NXX) for the serving central office and four
unique digits (XXXX).

Central office switches **11a-11n** utilize office equipment
(OE) numbers to identify specific equipment, such as physical
links or circuit connections.   For example, a subscriber's line
might terminate on a pair of terminals on the main distribution
frame of one of central office switches **11a-11n**.   The switch
identifies the terminals, and therefore a particular line, by an
OE number assigned to that terminal pair.   For a variety of

reasons, a service provider may assign different telephone numbers to the one line at the same or different times. For example, a local carrier may change the telephone number because a subscriber sells a house and a new subscriber moves in and receives a new number. However, the OE number for the terminals and thus the line itself remains the same.

On a normal call, a central office switch will detect an off-hook condition on a line and provide a dial tone. The switch identifies the line by the OE number. The central office switch retrieves profile information corresponding to the OE number and off-hook line. Then, the central office switch receives the dialed digits from the off-hook line terminal and routes the call. The central office switch may route the call over trunks and possibly through one or more central office switches to the central office switch that serves the called party's station or line. The switch terminating a call to a destination will also utilize profile information relating to the destination, for example to transfer the call if appropriate, to apply distinctive ringing, etc.

In the present invention, authentication of the identity of the caller is preferably initiated in IP **17** or telco application server **22**. Once a VID for a caller is received at a central office switch, a context inference application is initiated in IP **17** or telco application server **22**. The context inference service preferably requests a caller profile according to VID to determine billing information and personal information about the caller. In addition, the context inference service preferably determines the identity of the device utilized by accessing a device directory, prompting the caller to indicate the device identity, or other methods. Further, the location of the device

may be inferred from information provided by the central office switch originating the call, a GPS location, and the location assigned to a line number.  Other context information, such as the subject matter of a call and the role in which a caller is placing the call, are preferably determined as well.  The context information is preferably loaded with the VID at the central office switch.

The context information may be filtered at the central office switch according to general filtering preferences indicated by a caller in the caller profile.  In addition, context information may be filtered according to caller filtering preferences specifically selected for the callee.  Context information is then transferred with the call routed by one or more central office switches to a destination central office switch that services the called party's station or line.

Then, in the present invention, the context information is forwarded with a caller VID to the callee device.  The callee is enabled to determine whether to answer a call, transfer the call to voice mail, or select from other call handling options, based on knowing the identity of the caller and the context of the call.

In particular, the caller may provide the line number requested and/or may enter an identifier for the intended callee. A search engine may be accessed within IP **17** or telco application server **22** that queries at least one device associated with a callee to attempt to locate the intended callee.  A callee profile accessible according to the intended callee identity may include line number subscriptions and recently used line numbers, such that the search engine may query those line numbers to

locate the intended callee.

For purposes of the present invention, it is assumed that the intended callee is not available, or that the intended callee cannot answer all the caller's questions.  Therefore, the context inference service within IP **17** or telco application server **22** determines a context based backup for the call and transfers the call to the context based backup.

In addition, authentication of the identity of a callee answering the call is preferably initiated in IP **17** or telco application server **22**.  Once a RVID for a callee is received at a central office switch, a context inference application is initiated in IP **17** or telco application server **22** to determine the context of the callee side of a call.  The callee context information is preferably filtered according to callee preferences and transferred to the caller, such that the caller is provided with an identity of the callee.

As a call is forwarded or transferred to other callers and callees, IP **17** or telco application server **22** are preferably initiated to update the context for a call.  For example, the context may indicate the path of line number accessed in a call and whether the call was transferred or forwarded.

Referring now to **Figure 2**, there is illustrated a block diagram of an identity authentication and context inference system in accordance with the method, system, and program of the present invention.

Origin device **40** is utilized by a caller to initiate a call. The caller is prompted by the device performing caller

authentication to provide a voice utterance.  A VID for the
caller is provided to intermediary device **42** from the device
performing caller authentication.  The VID is utilized to access
a caller profile that includes service preferences and billing
information.  In addition, the VID is transmitted with the call
to destination device **44** for identifying the caller.

In general, caller identity authentication is performed by
receiving a voice utterance from a caller, analyzing the voice
utterance for sound qualities and content, and attempting to
match the sound qualities and content of a voice utterance to a
voice template previously recorded for a caller, to authenticate
the identity of the caller.  If there is a match between the
voice utterance and a voice template, then a VID is determined
for the caller and utilized to authenticate the caller identity
for retrieving a caller profile and billing the caller.  However,
in alternate embodiments, the identity of a caller may be
authenticated according to passwords, eye scans, encryption, and
other biometric methods.

Caller identity authentication may be initiated by origin
device **40**.  In particular, origin device **40** may include voice
templates and a feature for performing the caller identity
authentication.  In addition, origin device **40** may access a third
party server **48** via network **20**, where third party server **48** may
provide access to a database of voice templates and/or perform
the caller identity authentication.  Origin device **40** then
transmits a VID determined for the caller to intermediary device
**42** for use in specifying services and billing for a call from
origin device **40**.  Origin device **40** may include a caller
telephony device, a PBX, a call center, a private switching

system, network servers, feature servers, and other systems which provide call origination. Third party server **48** may include a telco application server, a generic application server, a database management system server, and other systems that function outside trusted telephone network **46**. In particular, intermediary device **42** may facilitate communication between origin device **40** and network **20**.

In addition, caller identity authentication may be initiated by intermediary device **42**. Intermediary device **42** may include database systems that store voice templates and an IP for performing caller identity authentication. In addition, intermediary device **42** may access telco application server **22** outside of trusted telephone network **46** via network **20**, where telco application server **22** provides a caller authentication service and/or provides access to a database of voice templates. Intermediary device **42** may include a PSTN switching network or networks. However, intermediary device **42** may also include a PBX, a call center, or other private switching system. Further, intermediary device **42** may include network servers, Websphere® (Websphere® is a registered trademark of International Business Machines Corporation) servers, and other systems which provide call processing.

Further, caller identity authentication may be initiated by destination device **44**. Destination device **44** may include voice templates and a feature for performing the caller identity authentication. In addition, destination device **44** may access a third party server **49** via network **20**, where third party server **49** may provide access to a database of voice templates and/or perform the caller identity authentication. Destination device

**44** will prompt a caller to provide a voice utterance at origin
device **40**, where intermediary device **42** facilitates
communications between origin device **40** and destination device
**44**.  Destination device **44** then determines and transmits a VID
for the caller to intermediary device **42** for use in specifying
services and billing for a call from origin device **40**.
Destination device **44** may include a callee telephony device, a
PBX, a call center, a private switching system, network servers,
feature servers, and other systems which provide call receipt.
Third party server **48** may include a telco application server, a
generic application server, a database management system server,
and other systems that function outside trusted telephone network
**46**.  In particular, intermediary device **42** may also facilitate
communication between destination device **44** and network **20**.

Similarly, a destination device **44** is utilized by a callee
to receive a call.  Advantageously, an authenticated identity of
the callee may be determined as an RVID.  Callee identity
authentication may be initiated by origin device **40**, intermediary
device **42**, or destination device **44**, in a manner similar to
initiation of caller identity authentication, as described above.

In particular, in the present invention, both the identity
of an intended callee and the identity of an accessed callee may
be determined in RVIDS.  The intended callee RVID may be
authenticated, for example, from a messaging system utilized by
the callee.

In addition to authenticating the identity of a caller or
callee in a VID or RVID, the context of the call is preferably
determined and transmitted as part of the VID or RVID or separate

therefrom. Origin device **40**, intermediary device **42**, telco application server **22**, and/or destination device **44** may include context inference services that perform context inference services. A context inference service may utilize context information gathered from multiple databases and may gathered context information directly from a caller or callee in response to prompts.

Context may include, but is not limited to, an intended callee, a subject matter of a call, a device identity, the location of an origin or destination device, billing information, service subscriptions, the path of a call, and other information which may provide a caller or callee with context of a call. Information for determining the context of a call may be gathered from a caller or callee profile, from routing information utilized by intermediary **42** from a device directory, from systems management server **28**, or other databases of information. The context inference service may, for example, infer the subject matter of a call as either business or personal based on the identity of the device from which a call originates and the location of that device. Alternatively, the subject of a call as either a business subject or personal subject may be inferred from the billing information context.

A VID or RVID may be transferred in multiple protocols, including, but not limited to, Interface Definition Language (IDL). A VID or RVID may include a range of information, where each type of information may be tagged or identified in some other manner. For example, the following tagged VID may be transmitted to represent an authenticated identity of a caller and context of the call:

    [caller name] Jon Smith

    [caller device] Jane Doe's cell phone

    [caller location] Central Time zone, Austin, TX

    [call subject] Project A

    [call billing] Jon Smith's business service provider C

    [intended callee name] Margie Heart

    [backup callee name] Mark Jones

    [authenticated by] Jane Doe's cell phone, service provider C


    In another example, the following tagged RVID may be
transmitted to the caller to represent an authenticated identity
of a callee and the context of the call, including the path of
the call:


    [backup callee name] Albert Jones

    [device] Albert Jones' home phone

    [location] Dallas, TX

    [path] call forwarded from 101-304-0000 to 214-333-1111


    With reference now to **Figure 3**, there is depicted a block
diagram of the flow of a call through a context inference system
in accordance with the method, system, and program of the present
invention.  As illustrated, origin device **40** transfers a call
request to intermediary device **42**.  The call request may be an
off-hook condition for a wireline device or a network service
connection request for a wireless device.

    Preferably, a switching service receiving the call request
establishes an origin call register **50** and retrieves a line
subscriber profile for the origin device line number.  The line
subscriber profile may be accessed from an SCP or a data storage
system external to trusted telephone network **46**.

Next, a context inference service may be initiated by the origin switching service. In particular, a context inference service **51** may be located within trusted telephone network **46** as an IP. Alternatively, a context inference service **51** may be located outside trusted telephone network **46** within a telco application server accessible via network **20**.

The context inference service preferably determines context for a call including, but not limited to, who is calling, an intended callee, the device utilized to place the call, the location of the caller, the billing method for the call, the path of the call, and/or the subject matter of the call. In addition, the context inference service preferably determines context for a call including, but not limited to, who receives a call, the path of line numbers utilized to access the callee, the device utilized to receive the call, the location of the callee, and the subject matter available for discussion by the callee. In addition, other categories of context may be determined.

To determine the context of the device utilized to place a call, the entity subscribing to the line number and/or an identifier for the device are preferably accessed. The first set of context clues is provided to the context inference service by the line subscriber profile. In particular, a line subscriber profile indicates the individual or business that subscribes to a particular line number. Further, a line subscriber profile may indicate that a business subscribes to a telephone service, but provide that service is subscribed to for use by a particular employee or group of employees.

In addition, the line subscriber profile indicates the

billing information and services subscribed to by the line
subscriber.  Billing information may provide context for whether
the line number is a business line or personal line.  In
addition, a billing context for a call may indicate the party
responsible for charges incurred in the call.

Further, a line subscriber profile preferably indicates
whether the line number is subscribed to for a wireline device, a
wireless device, or both.  Additional context information may be
inferred from whether a wireline or wireless device is utilized.

In addition to determining the identity of a person
associated with a line number, detecting and/or inferring the
identity of the device itself is particularly advantageous
context information.  Preferably the identity of the device may
be inferred from the line subscriber profile and other
information available.  A device identity may include a device
name, a line number utilized to access the device, and the device
type.  The device name may be assigned by the line subscriber and
output with a signal from the device.  Alternatively, the line
subscriber profile may indicate the device name.  The device type
may indicate the type of line utilized to access the device,
including, but not limited to, wireline, wireless, or
multiplexed.  In addition, the device type may indicate the type
of device accessed by the line including, but not limited to, a
car telephone line, a computer modem line, a PBX land line, a
residential line, a business line, or an Asymmetric Digital
Subscriber Line (ADSL) multiplexed line.

Further, determining or inferring the location of a device
is advantageous context information.  For a wireless device, the
location of a device may be determined most precisely where a GPS

tracking system is utilized by the origin device **40** or intermediary device **42**, to determine the exact geographical location of a caller.  For a wireline device, the location of the device is fixed according to the location the service is installed for the number.

In addition, for both a wireline and wireless device, a general location of the originated call may be determined from the geographical area covered by the switching center receiving the call.  Wireless devices are preferably provided service by a particular tower or other signal distribution point.  The geographical location and area covered by that tower may provide a general location of the origin of a call.  As the origin device moves from one wireless coverage area to another, the location may be updated.

The context inference service may infer additional context from location information.  For example, the time zone of the caller, the direction of movement of the caller, and other location related information may be inferred from location information.

In addition to extending a dial tone to a caller, an identity of the caller is preferably authenticated and loaded into origin call register **50**.  A caller profile accessed according to the VID is then accessed and loaded into origin call register **50**.  The context inference service preferably utilizes the caller profile and VID as additional context clues for the call.

In particular, in retrieving a caller profile according to VID, systems management server **28** may be accessed.  Systems

management server **28** preferably provides an interface through
which an individual may adjust preferences, select services, and
provide other information, which is stored and made accessible
according to the individual's VID. Systems management server **28**
may track services that an individual subscribes to, such as a
stock subscription service. In addition, systems management
server **28** allows an individual to adjust billing information and
view current charges according to VID.

The VID provides the context of who is placing the call.
The caller profile provides further context based on the billing
information and service subscriptions of the caller.

In addition, a caller profile may include preferences for
filtering context information depending on multiple factors.
Such factors may include, but are not limited to, the callee, the
device placing the call, the device receiving the call, the time
of day, a caller's schedule, and other variables selected by the
caller.

The subject matter of a call may be determined by prompting
a caller to provide a voice or text entry indicating the subject
matter of the call. Alternatively, the context inference service
may infer the subject matter of a call based on the caller's
schedule. The context inference service may also infer the
subject matter of a call based on the caller's business or the
business associated with the line number utilized by the caller.

In addition, a caller profile may include multiple roles
that a caller takes. For example, a caller may be a parent, a
business person, a coach, and a volunteer. The context inference

service may infer which role the caller is taking depending on other context or may prompt the caller to select a role. Further, the caller may select, at origin device **40**, a role for the call when placing the call request.

Advantageously, in the present invention, at least one backup callee may be determined for the intended callee according to the call context. A caller preferably provides a line number and/or an intended callee identity when placing a call request. Where a line number alone is provided, then the line subscriber profile preferably indicates backups for the line. Where a line number and intended callee identity are provided, then the intended callee profile preferably indicates backups for the callee, such as callee backups **55**. Callee backups **55** may be loaded into context inference service from a data storage system outside or inside trusted telephone network **46**.

In particular, callee or line subscriber backups preferably designate at least one backup party to receive the call if the intended callee is unavailable. The context inference service preferably selects at least one backup party from those available according to the context of the call. For example, if the call is from a client the context of the call indicates the relationship between the client and the intended callee, such that a business partner is selected as the backup for the call.

In the present invention, a caller may provide an intended callee identity, in lieu of a requested line number. In that case, intermediary device **42** preferably initiates a search engine service, such as search engine service **57** which is accessible within a telco application server. Alternatively, the search

engine service may be located in an Intelligent peripheral within trusted telephone network **46**.

Search engine **57** preferably queries at least one telephony device at which the intended callee may be available. For example, the search engine may query the telephony device in association with the intended callee RVID was most recently detected. In addition, the search engine may query those lines to which the intended callee is a subscriber. Further, search engine **57** may query other line numbers that the intended callee may be available at as determined for a schedule within the profile of the intended callee.

If search engine **57** is unable to locate the intended callee, then search engine **57** preferably indicates to context inference service **56** that the intended callee is unavailable. Context inference service **56** may then automatically transfer the call to a context based backup. In addition, context inference service **56** may prompt the caller to select from among multiple context based backups where multiple backups are available for the call.

In addition, in the present invention, a caller may request a line number for the call. In that case, intermediary device preferably transfers the call via a voice channel and the call context via a signal channel a destination service provider, where a destination call register **52** is established to terminate the call.

The destination service provider then transfers a signal to destination device **44** to announce the call. If the destination

service provider determines that call will not be answered, the destination service provider preferably responds to the call according to the context based backup selected by the context inference service. In particular, the destination service provider may transfer the call to another destination service provider for the context based backup.

The context information for the call is also transferred to destination device **44**, such that the callee is provided with a context for the call. The context information available in destination call register **52** may be filtered prior to transmittal to destination device **44** according to filtering preferences associated with the device, a line subscriber, or the callee. In addition, destination device **44** may filter the context displayed to a callee according to the device capabilities and preferences selected for the device.

Current relevant events for a callee may be determined as part of the context of a call. In particular, an electronic calendar may be accessed according to a callee identity from a caller profile or from an external calendaring data management system. In addition, where other devices are detected within a local network area of the origin device **40**, electronic schedules and other event information may be accessed about a current event for the caller from the other devices or according to the identities of other parties participating in an event with the caller.

For the present invention, a current relevant event may include a meeting, appointment, location, others involved in the event, duration of the event, and other information that describes the previous, current, or future environments in which

a callee may be located.  Scheduling may be utilized as a criteria for a backup callee.  For example, if a callee is detected on vacation, any calls received except from a select group of callers will automatically be transferred to a backup during a vacation time, while that individual may not be a backup with the callee is at work.  In another example, a history of talking times with different callers may be recorded, such that when a caller is detected, an estimated amount of time needed for the conversation with the caller may be determined and compared with the amount of time the callee has available on a calendar. If the callee does not have the estimated time available, then the call is transferred to a callee backup.

In one embodiment, a line may be answered by someone who is not the intended callee.  In that case, the caller may continue the call or request to be transferred to a context based backup by entering a voice command or keypad entry.  In addition, where the caller has provided an intended callee identity with the call request, if the RVID of the callee answering the call is not that of the intended callee, then a call transfer may be automatically invoked, with a message output to the callee indicating the reason for the transfer.

In particular, where multiple backups may be selected for the context of the call, the backups may be called sequentially and the call transferred to the first available backup, or the caller may be prompted to select from among the backups.

In another embodiment, where a backup is a messaging service, the messaging service preferably receives the call context, including other context based backups, such that the messaging service may offer the caller with options to select one

of the other available context based backups.

According to an advantage of the present invention, telephony devices may be equipped with selectable options, such that individuals may select an option indicating that the caller is unavailable.  When a call is received at the telephony device, the device preferably returns the unavailable signal, such that the destination service provider may automatically transfer the call to a context backup.

In a private switching network context, intermediary device **42** preferably functions as the private switching network enabled to detect context for a call and transfer the call to a backup at a line number not managed by the private switching network. Where backup transfers are made within the private switching network, it is advantageous to indicate to the caller that a transfer is being made and the name of the callee, but not to provide the line number of the callee to which the transfer is made in order to maintain the privacy of the callee.

According to other advantages of the present invention, the destination service provider may initiate at least one of context inference service **51** and context inference service **56** to determine the context of the recipient side of a call. Determining the context of the recipient side of a call may be performed in a manner similar to that described with reference to determining the context of the caller side of a call.  In addition, as will be further described, context inferences may be further enhanced when caller side and recipient side context information is combined.

In particular, the identity of the callee answering the call

is preferably authenticated and profiles accessed for the line line subscriber and/or callee.  Returning an RVID determined for the callee to the caller is advantageous because the RVID preferably includes the callee name and information about the transfer.

Referring now to **Figure 4**, there is depicted an illustrative example of a context based caller backup selection in accordance with the method, system, and program of the present invention. As illustrated, multiple types of context information may be accessed and determined by context inference service **56**.  In addition to the examples depicted, in alternate embodiments, other types of context information may be accessed and determined.

In the example, a call is placed by a caller AJane Smith@ to an intended callee AJon Doe@.  Authenticated caller identity **60** preferably provides context for who is placing the call. Intended callee **69** preferably provides context for who is intended to receive the call.  Alternate types of identification may be authenticated for the caller and intended callee.

A caller device identity **62** is preferably determined from line subscriber information.  In particular, the device name, line number utilized by the device, and device type are included. An intended callee may designate certain backups for wireless call and other backups for wireline calls, for example.

A call origination location **64** is preferably determined from a GPS position detected, from a geographical area supported by a service provider, from a caller schedule indicating a scheduled location, and other location related information accessible for a

call.  An intended callee may designate certain backups for calls received from one geographical area and other backups for calls received from another geographical area, for example.

A subject **65** is preferably determined from a scheduled event, from a type of device utilized, from the location of the caller, from previous subjects, and from caller selected subjects.  In addition, subjects may be inferred.  In the present example, the caller may select a particular student from a list of students about which the subject of the call pertains.  In addition, the caller profile may store a list of children and their parents, where a call to a parent infers the name of the child as a subject.  An intended callee may designate backups for different call subjects.

An intended callee backup profile **54** is preferably accessed from a callee profile according to an intended callee identifier. In the example, the intended callee, Jon Doe, has selected general backups and backups specified according to subject and time of day.  In the example, the RVIDS of backup callees are provided, such that access information for each backup callee is accessible.  Where a messaging service is an initial backup, the messaging service preferably receives context indicating other available backups and provides the caller with the option to leave a message, send a text message, or context one of the other selected backups.  Where the backup is an instant messaging service, the service preferably prompts the intended callee with an instant message at whatever computing system the intended callee is currently logged onto.

For the present call, the subject is a child.  Preferably, the backups selected by the intended callee for the subject

Achildren@ will be accessed.  Preferably, as illustrated, an
intended callee may rank the order in which the backup parties
are accessed.  Here, another parent, Susan Doe, is preferably
accessed first as a backup when Jon Doe is not available.

Context inference service **56** preferably filters the context
output according to the entity receiving the context.  For
example, filtered context to the intended callee **66** includes the
caller name, caller position, device name and subject of the
call.  If the callee answers the call, then the caller VID and
context are transferred to the intended callee.  In addition,
whether or not the callee answers, the filtered context is
preferably stored in the profile for the intended callee
according to the intended callee RVID.  Further, the filtered
context may be recorded and stored by a call management service
that monitors and records call information for billing and
verification purposes.

In addition, context inference service **56** may filter backup
context **61** provided to the service provider for transferring or
forwarding the call.  In particular, the backup context may be
transmitted in addition to other context for the call, but is
distinguished in the present invention for illustrative purposes.
Backup context **61** indicates the intended callee and the context
based backups selected for the intended callee, where the context
is children.  The origin service provider, destination service
provider, or a forwarding service preferably utilizes backup
context **61** to control transferring or forwarding of a call in the
event that the intended callee is unavailable.  In addition,
context inference service **56** may facilitate transferring or
forwarding the call from an intended callee service provider to a
backup callee service provider.

For purposes of the present invention, the intended callee
is unavailable and the call is transferred to Susan Doe,
according to backup context **61**.  Context inference service **56**
preferably receives and determines an authenticated backup callee
identity **70**, including an RVID name, RVID ID and RVID position.
Filtered context to the caller **63** includes the backup callee
name, backup callee position, and transfer path description.  In
the present invention it is advantageous to transfer filtered
context including a forwarding path to the caller when the call
is automatically forwarded to a backup.  In addition, since the
call may be transferred to a line where multiple callees may
answer the call, it is important to provide the caller with
verification that the current callee is the expected backup
callee.

In particular, in addition to loading the intended callee
backup preferences, a billing plan for the intended callee may be
accessed from the intended callee profile.  Advantageously, even
though a call is transferred, the intended callee may elect to
pay for any charges incurred by the backup callee for the call
according to a callee billing plan.  In addition, the intended
callee may agree to pay for a portion of incurred charges.  The
billing plan preferably includes service and account provider
selections, where accounts with providers are accessible
according to the intended callee RVID.

With reference now to **Figure 5**, there is illustrated a block
diagram of a context inference service in accordance with the
method, system, and program of the present invention.  Context
inference service **56** is preferably housed within a computing
system including at least a processor, memory, system software,

application software, and network software that execute to
provide a telco service.

In particular, context inference service **56** includes a
context inference engine **120**.  Context inference engine **120**
preferably determines the context for a call through information
accessible for the call and through inferences from that
information.  In addition, context inference engine **120** may
filter context information for each entity receiving that
information.

In the present invention, determining a context for a call
is particularly advantageous because backups for an intended
callee may be automatically selected according to the context of
the call.  A context based backup controller **122** preferably
facilitates context based backup selections according to backup
preferences of an intended callee and/or the backup preferences
assigned to a particular line number.  Context based backup
controller **122** may also facilitate querying backup callee parties
for availability before transferring the call to an available
backup party.  Moreover, context based backup controller **122** may
be initiated before or after it is determined that the intended
callee is unavailable.

A context database **124** preferably records and stores context
for each call processed by context inference service **56**.  Context
database **124** may be later accessed to provide verification and
context for billed call transactions.  In addition, context
database **124** may be accessed by context inference engine **120** or
context based backup controller **122** when determining context and
context backups, according to previous context.

An interactive voice recognition unit (IVRU) **126** preferably prompts the caller and callee to provide information required for determining context and detects caller or callee entries.  In addition, IVRU **126** preferably prompts the caller and callee to select from among multiple context based backups and detects selections.

Referring now to **Figure 6**, there is depicted a flow diagram of a signal flow and processing of a call in accordance with the method, system, and program of the present invention.  A standard telephone device is assumed for the Atel@ origin device and destination device in the present example.  However, a similar signal flow may be applied to other types of origin and destination devices, including server systems, private switching networks, and call centers.  Further, the flow is described with reference to wireline devices, however is not limited in application to wireline devices.

The caller lifts a handset creating an off-hook state in the origin device and a corresponding change in state of an off-hook signal to the central office (step S1).  In response to detecting an off-hook state in the origin device, the central office establishes a register for the call and requests a line subscriber profile from the SCP and/or an external network server (step S2).  A line subscriber profile including preferred services and a billing plan is returned to the central office (step S3).  The central office loads the line subscriber profile into the call register (step S4) and extends a dial tone to the origin device (step S5).

The origin device then transmits dialed digits to the

central office (step S6).  A caller may utilize a keypad to enter
a telephone number or utilize a voice dial feature if available.
In addition, a caller may provide an intended callee identifier.
Dialed digits may be received at other points in the process and
loaded into the call register until needed for processing the
call.

Next, the central office extends a caller authentication
service request to an IP or to the telco application server (step
S7).  The caller authentication server will prompt a caller to
provide a voice utterance, match the voice utterance with a voice
template and authenticate the caller identity as a VID which is
returned to the central office (step S8).  Alternatively, the
origin device or destination device may perform caller
authentication, where the VID is received from the origin device
or destination device.

Thereafter, the central office extends a call context
request to a context inference service available from an IP or
telco application server (step S9).  The context inference
service preferably accesses and loads a caller profile according
to VID into the origin call register.  Utilizing the line number,
line subscriber profile, VID and caller profile, the context
inference service preferably determines a context for the call.
In addition, the context inference service may access a backup
profile for an intended callee or intended line subscriber and
determine context based call backups should the intended callee
or line subscriber not be available.  The intended callee profile
may also indicate forwarding preferences designating whether the
call should be automatically forwarded to the context based
backups.  Where automatic forwarding is selected, the context
preferably selects a forwarding backup party identifier.

The context inference service preferably filters the context and designates certain portions of the context for receipt by certain entities.  The call context is returned to the origin central office (step S10).

Next, the context is loaded into the call register (step S11).  In addition, the context is filtered and distributed according to the entities receiving the context (step S12).  In particular, an IP or telco application server provide a filtering service.

A destination service provider for the call according to the dialed digits is determined from a directory (step S13).  Next, the call is transferred to the destination service provider with filtered context (step S14).  Alternatively, a search engine may send out queries to multiple line numbers searching for the callee.

Upon receiving a call at a destination service provider central office, a call register is established for the call and the line subscriber profile request is initiated to a SCP or external network database (step S15).  The line subscriber profile is returned to the central office (step S16) and loaded into the call register (step S17).

Next, a ring signal is extended to the destination device (step S18).  Here, an indication that the intended callee is unavailable is returned (step S19).  An unavailability signal may be generated by the telephony device according to a callee setting on the telephony device indication that the intended callee is Aaway from the desk@, Aout to lunch@, or otherwise unavailable.  In addition, after a particular number of rings, if

the call is not answered the telephony device may generate such as signal.  Moreover, the central office may determine unavailability after a particular number of rings.  Further, if the person answering the phone is not the intended callee, then unavailability may be determined.  In response to detecting unavailability, the backup callee service provider is preferably determined (step S20).  The call is then transferred to the backup service provider with filtered context (step S21).

The line subscriber profile for the backup party may be accessed, if the backup party is another callee.  The backup party may also include a messaging service for voice, text, or instant messaging.  After loading a profile, a ring signal is preferably extended to the backup callee device (step S22) and for purposes of the present example, the call is answered and an availability signal is returned to the backup callee destination central office (step S23).

A callee authentication request is extended to an IP or telco application server (step S24).  Alternatively, the destination device or origin device may initiate the callee authentication.  An RVID containing the authenticated identity of the backup callee is returned to the backup callee destination central office (step S25).

Next, a call context request is extended to an IP or telco application server (step S26).  A context inference service preferably adds to the context of the call according to backup callee profile information.  A filtered call context is returned to the backup callee destination central office (step S27).

The filtered call context may then be transferred to the

callee (step S28). Additionally, filtered call context may be transferred to the callee with a ring signal or at other times during the process. In addition, the filtered call context is preferably transferred to the caller to identify the callee and indicate the path of the call (step S29).

The call may then be processed according to the current call context (step S30). In particular, the call context may include billing plan selections, including sharing telephone service billing between the caller, the intended callee and the backup callee. In addition, the intended caller may transfer a payment to the backup callee for receiving transferred calls. The intended callee backup profile may include authorization for such a transfer or the backup callee may require such a transfer.

With reference now to **Figure 7**, there is depicted a high level logic flowchart of a process and program for controlling a context inference service in accordance with the method, system, and program of the present invention. As illustrated, the process starts at block **150** and thereafter proceeds to block **152**. Block **152** depicts a determination as to whether or not a context inference request is received. If a context inference request is not received, then the process iterates at block **152**. If a context inference request is received, then the process passes to block **154**.

Block **154** illustrates retrieving the line subscriber profiles, caller profiles, intended callee profiles, and other previous context between the caller and the line or intended callee. Next, block **156** depicts establishing a context for the call from the context clues retrieved and from information received from the caller in response to prompts for information

needed to determine a full call context.

Next, block **158** illustrates filtering a backup profile for the intended callee or line number according to the context. In particular, the backup profile may include backup parties designated according to context characteristics. Block **160** depicts selecting the context based backups for the call. Thereafter, block **162** illustrates indicating in the context whether the call is to be automatically forwarded to a context based backup. Preferably the intended callee may set a preference for automatic forwarding according to context or in general in the intended callee profile.

Thereafter, block **164** depicts determining and filtering context packets according to each recipient. In particular, some context information may be advantageous to transfer to the caller while other context information, such as backup party references, may be more advantageous to transfer to a service provider handling the call. Next, block **166** illustrates transferring the filtered context packets to the requesting service provider for distribution, and the process ends.

It is important to note that while the present invention has been described in the context of a fully functioning data processing system, those of ordinary skill in the art will appreciate that the processes of the present invention are capable of being distributed in the form of a computer readable medium of instructions and a variety of forms and that the present invention applies equally regardless of the particular type of signal bearing media actually used to carry out the distribution. Examples of computer readable media include recordable-type media, such as a floppy disk, a hard disk drive,

a RAM, CD-ROMs, DVD-ROMs, and transmission-type media, such as digital and analog communications links, wired or wireless communications links using transmission forms, such as, for example, radio frequency and light wave transmissions. The computer readable media may take the form of coded formats that are decoded for actual use in a particular data processing system.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.